

# KUGGREMSHJUL FÖR KONISK KLÄMBUSSNING L, H, XH

## TIMING BELT PULLEYS FOR TAPER BUSH L, H, XH

### H 200 - 1/2" (12.7 mm)

Utförande Version		Best Nr. Code	Typ Type	Bussning Bush	Max. Axelhål Max. Bore	Dp	De	Df	Dm	Di	F	S	R
Material: Stål Material: Steele		18 H 200F	5F	1210	35	72.77	71.39	79.5	-	52	58.0	25.0	33.0
		19 H 200F	5F	1210	35	76.81	75.44	83.0	-	56	58.0	25.0	33.0
		20 H 200F	5F	1610	42	80.55	79.48	87.0	-	60	58.0	25.0	33.0
Material: Gjutjärn Material: Cast Iron	Med Flänsar With Flanges	21 H 200F	5F	1610	42	84.89	83.52	91.0	-	64	58.0	25.0	33.0
		22 H 200F	5F	1610	42	88.94	87.56	94.0	-	68	58.0	25.0	33.0
		23 H 200F	5F	1610	42	92.98	91.61	102.0	-	71	58.0	25.0	33.0
		24 H 200F	5F	1610	42	97.02	95.65	102.0	-	74	58.0	25.0	33.0
		25 H 200F	5F	1610	42	101.06	99.69	112.0	-	78	58.0	25.0	33.0
		26 H 200F	5F	1610	42	105.11	103.73	112.0	-	82	58.0	25.0	33.0
		27 H 200F	5F	1610	42	109.15	107.78	120.0	-	87	58.0	25.0	33.0
		28 H 200F	5F	1610	42	113.19	111.82	120.0	-	91	58.0	25.0	33.0
		30 H 200F	5F	1610	42	121.28	119.90	128.0	-	99	58.0	25.0	33.0
		32 H 200F	5F	2012	50	129.36	127.99	135.0	-	107	58.0	32.0	26.0
		36 H 200F	5WF	2012	50	145.53	144.16	158.0	102	124	58.0	32.0	26.0
		40 H 200F	5WF	2012	50	161.70	160.33	168.0	106	140	58.0	32.0	26.0
		44 H 200F	5WF	2012	50	177.87	176.50	184.0	106	153	58.0	32.0	26.0
		48 H 200F	5WF	2517	60	194.04	192.67	200.0	119	169	58.0	45.0	13.0
		Utan Flänsar Without Flanges	60 H 200F	9A	2517	60	242.55	241.18	-	119	223	60.0	45.0
72 H 200F	9A		2517	60	291.06	289.69	-	119	270	60.0	45.0	7.5	
84 H 200F	9A		2517	60	339.57	338.20	-	119	320	60.0	45.0	7.5	
96 H 200F	9A		2517	60	388.08	386.71	-	119	366	60.0	45.0	7.5	
120 H 200F	9A		2517	60	485.10	483.73	-	119	462	60.0	45.0	7.5	

### H 300 - 1/2" (12.7 mm)

Utförande Version		Best Nr. Code	Typ Type	Bussning Bush	Max. Axelhål Max. Bore	Dp	De	Df	Dm	Di	F	S	R	
Material: Stål Material: Steele		20 H 300F	4F	1615	42	80.85	79.48	87	-	65	84.0	38.0	23.0	
		21 H 300F	4F	1615	42	84.89	83.52	91	-	66	84.0	38.0	23.0	
Material: Gjutjärn Materiale: Cast Iron	Med Flänsar With Flanges	22 H 300F	4F	1615	42	88.94	87.56	94	-	67	84.0	38.0	23.0	
		23 H 300F	4F	1615	42	92.98	91.61	102	-	71	84.0	38.0	23.0	
		24 H 300F	4F	1615	42	97.02	95.65	102	-	75	84.0	38.0	23.0	
		25 H 300F	4F	1615	42	101.06	99.69	112	-	79	84.0	38.0	23.0	
		26 H 300F	4F	1615	42	105.11	103.73	112	-	83	84.0	38.0	23.0	
		27 H 300F	4F	2012	50	109.15	107.78	120	-	87	84.0	32.0	26.0	
		28 H 300F	4F	2012	50	113.19	111.82	120	-	91	84.0	32.0	26.0	
		30 H 300F	4F	2012	50	121.28	119.90	128	-	99	84.0	32.0	26.0	
		32 H 300F	4F	2517	60	129.36	127.99	135	-	107	84.0	45.0	19.5	
		36 H 300F	4F	2517	60	145.53	144.16	158	-	124	84.0	45.0	19.5	
		40 H 300F	4F	2517	60	161.70	160.33	168	-	137	84.0	45.0	19.5	
		44 H 300F	4WF	2517	60	177.87	176.50	184	119	153	86.0	45.0	20.5	
		48 H 300F	4WF	2517	60	194.04	192.67	200	119	169	86.0	45.0	20.5	
		Utan Flänsar Without Flanges	60 H 300F	9A	2517	60	242.55	241.18	-	119	223	86.0	45.0	20.5
			72 H 300F	9A	2517	60	291.06	289.69	-	119	270	86.0	45.0	20.5
			84 H 300F	9A	2517	60	339.57	338.20	-	119	320	86.0	45.0	20.5
			96 H 300F	9A	3030	75	388.08	386.71	-	150	362	86.0	76.0	5.0
			120 H 300F	9A	3030	75	485.10	483.73	-	150	460	86.0	76.0	5.0