

KUGGREMSHJUL FÖR KONISK KLÄMBUSSNING L, H, XH

TIMING BELT PULLEYS FOR TAPER BUSH L, H, XH

XH 200 - 7/8" (22.225 mm)

Utförande Version	Best Nr. Code	Typ Type	Bussning Bush	Max. Axelhål Max. Bore	Dp	De	Df	Dm	Di	F	S	R	
Material: Gjutjärn Materiale: Cast Iron	Med Flänsar With Flanges	18 XH 200F	5F	2517	60	127.34	124.55	142	-	95	64	45	19.0
		20 XH 200F	5F	2517	60	141.49	138.69	158	-	110	64	45	19.0
		22 XH 200F	5F	2517	60	155.64	152.84	168	-	120	64	45	19.0
		24 XH 200F	5F	2517	60	169.79	166.99	184	-	135	64	45	19.0
		26 XH 200F	5F	2517	60	183.94	181.14	200	-	150	64	45	19.0
		28 XH 200F	4WF	2517	60	198.08	195.29	211	120	165	64	45	9.5
		30 XH 200F	4WF	2517	60	212.23	209.44	226	120	180	64	45	9.5
		32 XH 200F	4WF	2517	60	226.38	223.59	240	120	195	64	45	9.5
	40 XH 200F	4WF	3020	75	282.98	280.18	296	160	245	64	51	6.5	
	Utan Flänsar Without Flanges	48 XH 200F	9W	3020	75	339.57	336.78	-	160	300	64	51	6.5
		60 XH 200F	7A	3535	90	424.47	421.67	-	190	385	64	89	12.5
		72 XH 200F	7A	3535	90	509.36	506.56	-	190	470	64	89	12.5
		84 XH 200F	7A	3535	90	594.25	591.46	-	190	555	64	89	12.5
		96 XH 200F	7A	3535	90	679.15	676.35	-	190	640	64	89	12.5
		120 XH 200F	7A	3535	90	848.93	846.14	-	190	810	64	89	12.5

XH 300 - 7/8" (22.225 mm)

Utförande Version	Best Nr. Code	Typ Type	Bussning Bush	Max. Axelhål Max. Bore	Dp	De	Df	Dm	Di	F	S	R	
Material: Gjutjärn Materiale: Cast Iron	Med Flänsar With Flanges	18 XH 300F	5F	2517	60	127.34	124.55	142	-	95	90	45	45.0
		20 XH 300F	5F	2517	60	141.49	138.69	158	-	110	90	45	45.0
		22 XH 300F	5F	2517	60	155.64	152.84	168	-	120	90	45	45.0
		24 XH 300F	5F	2517	60	169.79	166.99	184	-	135	90	45	45.0
		26 XH 300F	5F	2517	60	183.94	181.14	200	-	150	90	45	45.0
		28 XH 300F	5F	3020	75	198.08	195.29	211	-	165	90	51	39.0
		30 XH 300F	5F	3020	75	212.23	209.24	226	-	180	90	51	39.0
		32 XH 300F	5F	3020	75	226.38	223.59	240	-	195	50	51	39.0
	40 XH 300F	4WF	3020	75	282.98	280.18	296	160	245	90	51	19.5	
	Utan Flänsar Without Flanges	48 XH 300F	9A	3020	75	339.57	336.78	-	160	300	90	51	19.5
		60 XH 300F	9A	3535	90	424.47	421.67	-	190	385	90	89	0.5
		72 XH 300F	9A	3535	90	509.36	506.56	-	190	470	90	89	0.5
		84 XH 300F	7A	4040	100	594.25	591.46	-	230	555	90	102	6.0
		96 XH 300F	7A	4040	100	679.15	676.35	-	230	640	90	102	6.0
		120 XH 300F	7A	4040	100	848.93	846.14	-	230	810	90	102	6.0

XH 400 - 7/8" (22.225 mm)

Utförande Version	Best Nr. Code	Typ Type	Bussning Bush	Max. Axelhål Max. Bore	Dp	De	Df	Dm	Di	F	S	R	
Material: Gjutjärn Materiale: Cast Iron	Med Flänsar With Flanges	18 XH 400F	5F	2517	60	127.34	124.55	142	-	95	119	45	74.0
		20 XH 400F	5F	2517	60	141.49	138.69	158	-	110	119	45	74.0
		22 XH 400F	5F	2517	60	155.64	152.84	168	-	120	119	45	74.0
		24 XH 400F	5F	3020	75	169.79	166.99	184	-	135	119	51	68.0
		26 XH 400F	5F	3020	75	183.94	181.14	200	-	150	119	51	68.0
		28 XH 400F	5F	3020	75	198.08	195.29	211	-	165	119	51	68.0
		30 XH 400F	5F	3020	75	212.23	209.44	226	-	180	119	51	68.0
		32 XH 400F	5F	3020	75	226.38	223.59	240	-	195	119	51	68.0
	40 XH 400F	4WF	3535	90	282.98	280.18	296	190	245	119	89	15.0	
	Utan Flänsar Without Flanges	48 XH 400F	9W	3535	90	339.57	336.78	-	190	300	119	89	15.0
		60 XH 400F	9A	4040	100	424.47	421.67	-	230	385	119	102	8.5
		72 XH 400F	9A	4040	100	509.36	506.56	-	230	470	119	102	8.5
		84 XH 400F	9A	4040	100	594.25	591.46	-	230	555	119	102	8.5
		96 XH 400F	9A	4040	100	679.15	676.35	-	230	640	119	102	8.5
		120 XH 400F	9A	4040	100	848.93	846.14	-	230	810	119	102	8.5