

## TEKNISK INFO, PROFIL XL, L, H, XH

### TECHNICAL INFORMATION, PROFILE XL, L, H, XH

#### Effekttabell för profil H / Power table profile H

Varvtal n1 R.P.M. n1	Tandantal lilla hjulet / No. of teeth small pulley																
	16H	18H	19H	20H	21H	22H	23H	24H	25H	26H	27H	28H	30	32H	36H	40H	48H
100	0.21	0.24	0.25	0.26	0.28	0.29	0.30	0.32	0.33	0.34	0.36	0.37	0.40	0.42	0.47	0.53	0.63
200	0.43	0.47	0.50	0.53	0.55	0.58	0.61	0.63	0.66	0.69	0.71	0.74	0.79	0.84	0.95	1.05	1.26
300	0.63	0.71	0.75	0.79	0.83	0.87	0.91	0.95	0.99	1.03	1.07	1.11	1.19	1.26	1.42	1.58	1.89
400	0.84	0.95	1.00	1.05	1.11	1.16	1.21	1.26	1.32	1.37	1.42	1.47	1.58	1.68	1.89	2.10	2.52
500	1.05	1.19	1.25	1.32	1.38	1.45	1.51	1.58	1.65	1.71	1.78	1.84	1.97	2.10	2.37	2.63	3.15
600	1.27	1.42	1.50	1.58	1.66	1.74	1.82	1.89	1.97	2.05	2.13	2.21	2.37	2.52	2.83	3.15	3.77
700	1.48	1.66	1.75	1.84	1.93	2.03	2.12	2.21	2.30	2.39	2.48	2.57	2.76	2.94	3.30	3.66	4.38
800	1.69	1.89	2.00	2.10	2.21	2.31	2.42	2.52	2.63	2.73	2.83	2.94	3.15	3.35	3.77	4.18	4.99
900	1.90	2.13	2.25	2.37	2.48	2.60	2.72	2.83	2.95	3.07	3.18	3.30	3.53	3.77	4.23	4.69	5.59
1000	2.10	2.37	2.50	2.63	2.76	2.89	3.02	3.15	3.26	3.40	3.53	3.66	3.92	4.18	4.69	5.19	6.19
1200	2.52	2.82	2.99	3.15	3.30	3.46	3.61	3.77	3.92	4.07	4.23	4.38	4.69	4.99	5.59	6.19	7.35
1400	2.94	3.30	3.48	3.66	3.84	4.02	4.20	4.38	4.56	4.74	4.91	5.09	5.44	5.79	6.48	7.16	8.47
1600	3.36	3.77	3.97	4.18	4.38	4.58	4.79	4.99	5.19	5.39	5.59	5.79	6.19	6.58	7.35	8.10	9.55
1800	3.77	4.23	4.46	4.69	4.91	5.14	5.37	5.59	5.82	6.04	6.26	6.48	6.92	7.35	8.20	9.02	10.57
2000	4.18	4.69	4.94	5.19	5.44	5.69	5.94	6.19	6.43	6.68	6.92	7.16	7.64	8.10	9.02	9.89	11.53
2200		5.14	5.42	5.69	5.96	6.24	6.51	6.77	7.04	7.30	7.56	7.82	8.34	8.84	9.81	10.73	12.47
2400		5.60	5.86	6.19	6.48	6.77	7.06	7.35	7.63	7.92	8.20	8.47	9.02	9.55	10.57	11.53	13.24
2600		6.04	6.36	6.68	6.99	7.30	7.61	7.92	8.22	8.52	8.81	9.11	9.68	10.24	11.30	12.28	13.99
2800		6.49	6.82	7.16	7.49	7.82	8.15	8.47	8.79	9.11	9.42	9.72	10.32	10.90	11.99	12.98	14.64
3000		6.93	7.28	7.63	7.99	8.33	8.68	9.03	9.35	9.68	10.00	10.32	10.94	11.53	12.64	13.62	15.20
3200		7.35	7.73	8.10	8.47	8.84	9.20	9.55	9.90	10.24	10.57	10.90	11.53	12.13	13.24	14.22	15.66
3400		7.78	8.17	8.56	8.95	9.33	9.70	10.07	10.42	10.78	11.12	11.45	12.10	12.71	13.82	14.74	16.01
3800				9.46	9.87	10.28	10.67	11.06	11.43	11.80	12.15	12.49	13.15	13.74	14.81	15.58	16.35
4000				9.88	10.32	10.73	11.14	11.53	11.91	12.28	12.64	12.98	13.62	14.20	15.22	15.39	16.34
4400				10.72	11.18	11.61	12.02	12.42	12.81	13.18	13.53	13.89	14.49	15.01	15.87	16.29	15.90
4600				11.12	11.59	12.02	12.44	12.84	13.23	13.59	13.94	14.29	14.84	15.35	16.10	16.35	15.46
5000				11.89	12.36	12.81	13.23	13.62	13.97	14.34	14.67	15.00	15.49	15.88	16.37	16.21	-
5400				12.60	13.08	13.53	13.91	14.27	14.63	14.99	15.28	15.59	15.96	16.21	16.36	15.68	-
6000				13.57	14.04	14.51	14.81	15.12	15.43	15.87	15.96	16.19	13.32	16.30	15.82	-	-

#### Angivet värde i kW / tum / Values per 1" width in kW

Rembredd i tum / Belt width in inch	0.71	0.86	1.0	1.29	1.56	1.84	2.14	2.72	3.36	4.06	4.76	6.15
Rembreddsfaktor / Belt width factor	075•	087	100•	125	150•	175	200•	250	300•	350	400	500

#### Effekttabell för profil XH / Power table profile XH

Varvtal n1 R.P.M. n1	Tandantal lilla hjulet / No. of teeth small pulley								
	18XH	20XH	22XH	24XH	26XH	28XH	30XH	32XH	40XH
100	0.57	0.63	0.69	0.76	0.82	0.88	0.94	1.01	1.26
200	1.13	1.26	1.38	1.51	1.63	1.76	1.88	2.01	2.51
300	1.70	1.88	2.07	2.26	2.45	2.63	2.82	3.01	3.75
400	2.26	2.51	2.76	3.01	3.25	3.50	3.75	4.00	4.97
500	2.82	3.13	3.44	3.75	4.06	4.36	4.67	4.97	6.17
600	3.38	3.75	4.12	4.48	4.85	5.21	5.57	5.93	7.33
700	3.93	4.36	4.79	5.21	5.63	6.05	6.46	6.87	8.46
800	4.48	4.97	5.45	5.93	6.40	6.87	7.33	7.79	9.55
900	5.03	5.57	6.11	6.64	7.16	7.68	8.18	8.68	10.59
1000	5.57	6.16	6.75	7.33	7.90	8.46	9.01	9.55	11.57
1200		7.34	8.02	8.69	9.34	9.97	10.59	11.19	13.35
1400		8.47	9.23	9.98	10.69	11.38	12.04	12.67	14.83
1600		9.55	10.39	11.19	11.95	12.67	13.35	13.98	15.98
1800			11.47	12.32	13.10	13.83	14.49	15.08	16.67
2000			12.49	13.35	14.13	14.84	15.45	15.98	17.04
2400			14.28	15.08	15.77	16.32	16.73	16.97	16.15
3000				16.73	17.01	17.02	18.74	16.15	

#### Angivet värde i kW / tum / Values per 1" width in kW

Rembredd i tum / Belt width in inch	2.14	2.72	3.36	4.06	4.76	6.15	7.50	8.89	10.32
Rembreddsfaktor / Belt width factor	200•	250	300•	350	400•	500•	600	700	800