

# KUGGREMSHJUL FÖRBORRADE, HTD

## TIMING BELT PULLEYS STANDARD, HTD

### HTD 5M-15

Utförande Version	Best Nr. Code	Typ Type	Tandantal No. of teeth	Dp	De	Df	Dm	F	L	d	
Material: Stål Materiale: Steele	Med Flänsar With Flanges	12-5M-15FB	6F	12	19.10	17.96	23	13.0	20.5	26	4
		14-5M-15FB	6F	14	22.28	21.14	25	14.0	20.5	26	6
		15-5M-15FB	6F	15	23.87	22.73	28	16.0	20.5	26	6
		16-5M-15FB	6F	16	25.46	24.32	28	16.5	20.5	26	6
		18-5M-15FB	6F	18	28.65	27.51	32	20.0	20.5	26	6
		20-5M-15FB	6F	20	31.83	30.69	37	23.0	20.5	26	6
		21-5M-15FB	6F	21	33.42	32.28	38	24.0	20.5	26	6
		22-5M-15FB	6F	22	35.01	33.87	38	25.5	20.5	26	6
		24-5M-15FB	6F	24	38.20	37.06	43	27.0	20.5	28	6
		26-5M-15FB	6F	26	41.38	40.24	44	30.0	20.5	28	6
		28-5M-15FB	6F	28	44.56	43.42	48	30.5	20.5	28	6
		30-5M-15FB	6F	30	47.75	46.60	51	35.0	20.5	28	6
		32-5M-15FB	6F	32	50.93	49.79	54	38.0	20.5	28	8
		36-5M-15FB	6F	36	57.30	56.16	60	38.0	20.5	28	8
		40-5M-15FB	6F	40	63.66	62.52	70	38.0	20.5	28	8
Material: Aluminium Materiale: Aluminium	Utan Flänsar Without Flanges	44-5M-15FB	6W	44	70.03	68.89	-	38.0	20.5	30	8
		48-5M-15FB	6W	48	76.39	75.25	-	38.0	20.5	30	8
		60-5M-15FB	6W	60	95.49	94.35	-	50.0	20.5	30	8
		72-5M-15FB	6W	72	114.59	113.45	-	50.0	20.5	30	8

### HTD 5M-25

Utförande Version	Best Nr. Code	Typ Type	Tandantal No. of teeth	Dp	De	Df	Dm	F	L	d	
Material: Stål Materiale: Steele	Med Flänsar With Flanges	12-5M-25FB	6F	12	19.10	17.96	23	13.0	30.5	36.0	4
		14-5M-25FB	6F	14	22.28	21.14	25	14.0	30.5	36.0	6
		15-5M-25FB	6F	15	23.87	22.73	28	16.0	30.5	36.0	6
		16-5M-25FB	6F	16	25.46	24.32	28	16.5	30.5	36.0	6
		18-5M-25FB	6F	18	28.65	27.51	32	20.0	30.5	36.0	6
		20-5M-25FB	6F	20	31.83	30.69	37	23.0	30.5	36.5	6
		21-5M-25FB	6F	21	33.42	32.28	38	24.0	30.5	38.5	6
		22-5M-25FB	6F	22	35.01	33.87	38	25.5	30.5	38.5	6
		24-5M-25FB	6F	24	38.20	37.06	43	27.0	30.5	38.5	6
		26-5M-25FB	6F	26	41.38	40.24	44	30.0	30.5	38.5	6
		28-5M-25FB	6F	28	44.56	43.42	48	30.5	30.5	38.5	6
		30-5M-25FB	6F	30	47.75	46.60	51	35.0	30.5	38.5	6
		32-5M-25FB	6F	32	50.93	49.79	54	38.0	30.5	38.5	8
		36-5M-25FB	6F	36	57.30	56.16	60	38.0	30.5	38.5	8
		40-5M-25FB	6F	40	63.66	62.52	70	38.0	30.5	38.5	8
Material: Aluminium Materiale: Aluminium	Utan Flänsar Without Flanges	44-5M-25FB	6W	44	70.03	68.89	-	38.0	30.5	40.5	8
		48-5M-25FB	6W	48	76.39	75.25	-	38.0	30.5	40.5	8
		60-5M-25FB	6W	60	95.49	94.35	-	50.0	30.5	40.5	8
		72-5M-25FB	6W	72	114.59	113.45	-	50.0	30.5	40.5	8