

KUGGREMSHJUL FÖRBORRADE, HTD

TIMING BELT PULLEYS STANDARD, HTD

HTD 8M-20

| Utförande Version | Best. Nr. Code | Typ Type | Tandantal No. of teeth | Dp | De | Df | Dm | Di | F | L | d | |
|--|---------------------------------|-------------|---------------------------|--------|--------|--------|-----|-----|-----|----|----|----|
| Material: Gjutjärn Materiale: Cast iron | Med Flänsar With Flanges | 22-8M-20FB | 6F | 22 | 56.02 | 54.65 | 60 | 43 | - | 28 | 38 | 12 |
| | | 24-8M-20FB | 6F | 24 | 61.12 | 59.75 | 67 | 45 | - | 28 | 38 | 12 |
| | | 26-8M-20FB | 6F | 26 | 66.21 | 64.84 | 70 | 50 | - | 28 | 38 | 12 |
| | | 28-8M-20FB | 6F | 28 | 71.30 | 70.08 | 75 | 50 | - | 28 | 38 | 15 |
| | | 30-8M-20FB | 6F | 30 | 76.39 | 75.13 | 83 | 55 | - | 28 | 38 | 15 |
| | | 32-8M-20FB | 6F | 32 | 81.49 | 80.16 | 87 | 60 | - | 28 | 38 | 15 |
| | | 34-8M-20FB | 6F | 34 | 86.58 | 85.22 | 91 | 70 | - | 28 | 38 | 15 |
| | | 36-8M-20FB | 6F | 36 | 91.67 | 90.30 | 97 | 70 | - | 28 | 38 | 15 |
| | | 38-8M-20FB | 6F | 38 | 96.77 | 95.39 | 102 | 75 | - | 28 | 38 | 15 |
| | | 40-8M-20FB | 6F | 40 | 101.86 | 100.49 | 106 | 75 | - | 28 | 38 | 15 |
| | | 44-8M-20FB | 6F | 44 | 112.05 | 110.67 | 120 | 75 | - | 28 | 38 | 15 |
| | | 48-8M-20FB | 6F | 48 | 122.23 | 120.86 | 128 | 75 | - | 28 | 38 | 15 |
| | | 56-8M-20FB | 6WF | 56 | 142.60 | 141.23 | 150 | 80 | 117 | 28 | 38 | 15 |
| | | 64-8M-20FB | 6WF | 64 | 162.97 | 161.60 | 168 | 80 | 137 | 28 | 38 | 15 |
| | | 72-8M-20FB | 6AF | 72 | 183.35 | 181.97 | 192 | 80 | 158 | 28 | 38 | 15 |
| | Utan Flänsar Without Flanges | 80-8M-20FB | 6A | 80 | 203.72 | 202.35 | - | 90 | 180 | 28 | 38 | 15 |
| | | 90-8M-20FB | 6A | 90 | 229.18 | 227.81 | - | 90 | 204 | 28 | 38 | 15 |
| | | 112-8M-20FB | 6A | 112 | 285.21 | 283.83 | - | 90 | 260 | 28 | 38 | 18 |
| | | 144-8M-20FB | 6A | 144 | 366.69 | 365.32 | - | 90 | 341 | 28 | 38 | 20 |
| | | 168-8M-20FB | 6A | 168 | 427.81 | 426.44 | - | 100 | 402 | 28 | 38 | 20 |
| 192-8M-20FB | 6A | 192 | 488.92 | 487.55 | - | 100 | 463 | 28 | 38 | 20 | | |

HTD 8M-30

| Utförande Version | Best. Nr. Code | Typ Type | Tandantal No. of teeth | Dp | De | Df | Dm | Di | F | L | d | |
|--|---------------------------------|-------------|---------------------------|--------|--------|--------|-----|-----|-----|----|----|----|
| Material: Gjutjärn Materiale: Cast iron | Med Flänsar With Flanges | 22-8M-30FB | 6F | 22 | 56.02 | 54.65 | 60 | 43 | - | 38 | 48 | 12 |
| | | 24-8M-30FB | 6F | 24 | 61.12 | 59.75 | 67 | 45 | - | 38 | 48 | 12 |
| | | 26-8M-30FB | 6F | 26 | 66.21 | 64.84 | 70 | 50 | - | 38 | 48 | 12 |
| | | 28-8M-30FB | 6F | 28 | 71.30 | 70.08 | 75 | 50 | - | 38 | 48 | 15 |
| | | 30-8M-30FB | 6F | 30 | 76.39 | 75.13 | 83 | 55 | - | 38 | 48 | 15 |
| | | 32-8M-30FB | 6F | 32 | 81.49 | 80.16 | 87 | 60 | - | 38 | 48 | 15 |
| | | 34-8M-30FB | 6F | 34 | 86.58 | 85.22 | 91 | 70 | - | 38 | 48 | 15 |
| | | 36-8M-30FB | 6F | 36 | 91.67 | 90.30 | 97 | 70 | - | 38 | 48 | 15 |
| | | 38-8M-30FB | 6F | 38 | 96.77 | 95.39 | 102 | 75 | - | 38 | 48 | 15 |
| | | 40-8M-30FB | 6F | 40 | 101.86 | 100.49 | 106 | 75 | - | 38 | 48 | 15 |
| | | 44-8M-30FB | 6F | 44 | 112.05 | 110.67 | 120 | 75 | - | 38 | 48 | 15 |
| | | 48-8M-30FB | 6F | 48 | 122.23 | 120.86 | 128 | 75 | - | 38 | 48 | 15 |
| | | 56-8M-30FB | 6WF | 56 | 142.60 | 141.23 | 150 | 90 | 117 | 38 | 48 | 15 |
| | | 64-8M-30FB | 6WF | 64 | 162.97 | 161.60 | 168 | 90 | 137 | 38 | 48 | 15 |
| | | 72-8M-30FB | 6AF | 72 | 183.35 | 181.97 | 192 | 95 | 158 | 38 | 48 | 15 |
| | Utan Flänsar Without Flanges | 80-8M-30FB | 6A | 80 | 203.72 | 202.35 | - | 100 | 180 | 38 | 48 | 15 |
| | | 90-8M-30FB | 6A | 90 | 229.18 | 227.81 | - | 100 | 204 | 38 | 48 | 15 |
| | | 112-8M-30FB | 6A | 112 | 285.21 | 283.83 | - | 100 | 260 | 38 | 48 | 18 |
| | | 144-8M-30FB | 6A | 144 | 366.69 | 365.32 | - | 100 | 341 | 38 | 48 | 20 |
| | | 168-8M-30FB | 6A | 168 | 427.81 | 426.44 | - | 100 | 402 | 38 | 48 | 20 |
| 192-8M-30FB | 6A | 192 | 488.92 | 487.55 | - | 100 | 463 | 38 | 48 | 20 | | |