

# KUGGREMSHJUL FÖRBORRADE, PROFIL MXL, XL, L, H, XH

## TIMING BELT PULLEYS STANDARD, PROFILE MXL, XL, L, H, XH

### L 050

Utförande Version	Best Nr. Code	Typ Type	Tandantal No. of teeth	Dp	De	Df	Dm	Di	F	L	d			
Material: Stål Materiale: Steele	Med Flänsar With Flanges	10L050FB	6F	10	30.32	29.56	37.0	20	-	19.0	28	8		
		11L050FB	6F	11	33.35	32.59	37.0	24	-	19.0	30	8		
		12L050FB	6F	12	36.38	35.62	43.0	24	-	19.0	30	8		
		13L050FB	6F	13	39.41	38.65	43.0	28	-	19.0	30	8		
		14L050FB	6F	14	42.45	41.68	48.0	28	-	19.0	30	12		
		15L050FB	6F	15	45.48	44.72	51.0	34	-	19.0	30	12		
		16L050FB	6F	16	48.51	47.75	54.0	36	-	19.0	32	12		
		17L050FB	6F	17	51.54	50.78	57.0	36	-	19.0	32	12		
		18L050FB	6F	18	54.57	53.81	60.0	40	-	19.0	32	12		
		19L050FB	6F	19	57.61	56.84	62.5	40	-	19.0	32	12		
		20L050FB	6F	20	60.64	59.88	67.0	40	-	19.0	32	12		
		21L050FB	6F	21	63.67	62.91	70.0	45	-	19.0	32	12		
		22L050FB	6F	22	66.70	65.94	75.0	45	-	19.0	32	12		
		23L050FB	6F	23	69.73	68.97	79.5	55	-	19.0	32	12		
		24L050FB	6F	24	72.77	72.00	79.0	55	-	19.0	32	12		
		25L050FB	6F	25	75.80	75.04	83.0	58	-	19.0	32	12		
		26L050FB	6F	26	78.83	78.07	87.0	58	-	19.0	32	12		
		27L050FB	6F	27	81.86	81.10	91.0	58	-	19.0	32	12		
		28L050FB	6F	28	84.89	84.13	91.0	58	-	19.0	32	12		
		29L050FB	6F	29	87.93	87.16	91.0	58	-	19.0	32	12		
		30L050FB	6F	30	90.96	90.20	97.0	70	-	19.0	32	12		
		32L050FB	6F	32	97.02	96.26	102.0	70	-	19.0	32	12		
		Material: Gjutjärn Materiale: Cast Iron	Med Flänsar With Flanges	33L050FB	6F	33	100.05	99.26	112.0	70	-	19.0	32	14
				34L050FB	6F	34	103.08	102.32	115.0	70	-	19.0	32	14
				35L050FB	6F	35	106.12	105.35	115.0	70	-	19.0	32	14
				36L050FB	6F	36	109.15	108.39	120.0	70	-	19.0	32	14
				40L050FB	6WF	40	121.28	120.51	128.0	70	100	19.0	32	14
				41L050FB	6WF	41	124.31	123.55	135.0	70	103	19.0	32	14
				42L050FB	6WF	42	127.34	126.58	135.0	70	106	19.0	32	14
				44L050FB	6WF	44	133.40	132.64	142.0	70	112	19.0	32	14
				45L050FB	6WF	45	136.44	135.67	142.0	70	115	19.0	32	14
				47L050FB	6WF	47	142.50	141.74	150.0	70	121	19.0	32	14
48L050FB	6WF		48	145.53	144.77	150.0	70	124	19.0	32	14			
Utan Flänsar Without Flanges	49L050FB		6W	49	148.56	147.80	-	70	127	19.0	32	14		
	50L050FB		6W	50	151.60	150.83	-	70	130	19.0	32	14		
	52L050FB		6W	52	157.66	156.90	-	70	136	19.0	32	14		
	56L050FB		6W	56	169.79	169.02	-	70	149	19.0	32	14		
	57L050FB		6W	57	172.82	172.06	-	70	152	19.0	32	14		
	60L050FB		6W	60	181.91	181.15	-	75	160	19.0	42	16		
	65L050FB		6A	65	197.07	196.31	-	75	176	19.0	42	16		
	66L050FB		6A	66	200.11	199.34	-	75	179	19.0	42	16		
	72L050FB		6A	72	218.30	217.53	-	75	197	19.0	42	16		
	84L050FB	6A	84	254.68	253.92	-	75	233	19.0	42	16			
90L050FB	6A	90	272.87	272.11	-	75	252	19.0	42	16				
96L050FB	6A	96	291.06	290.30	-	75	269	19.0	42	16				
120L050FB	6A	120	363.83	363.07	-	75	342	19.0	42	16				

### L 075

Utförande Version	Best Nr. Code	Typ Type	Tandantal No. of teeth	Dp	De	Df	Dm	Di	F	L	d			
Material: Stål Materiale: Steele	Med Flänsar With Flanges	10L075FB	6F	10	30.32	29.56	37.0	20	-	25.4	38	8		
		11L075FB	6F	11	33.35	32.59	37.0	24	-	25.4	38	8		
		12L075FB	6F	12	36.38	35.62	43.0	24	-	25.4	38	10		
		13L075FB	6F	13	39.41	38.65	43.0	28	-	25.4	38	10		
		14L075FB	6F	14	42.45	41.68	48.0	28	-	25.4	38	12		
		15L075FB	6F	15	45.48	44.72	51.0	34	-	25.4	38	12		
		16L075FB	6F	16	48.51	47.75	54.0	36	-	25.4	38	12		
		17L075FB	6F	17	51.54	50.78	57.0	36	-	25.4	38	12		
		18L075FB	6F	18	54.57	53.81	60.0	40	-	25.4	38	12		
		19L075FB	6F	19	57.61	56.84	62.5	40	-	25.4	38	12		
		20L075FB	6F	20	60.64	59.88	67.0	40	-	25.4	38	14		
		21L075FB	6F	21	63.67	62.91	70.0	45	-	25.4	38	14		
		22L075FB	6F	22	66.70	65.94	75.0	45	-	25.4	38	14		
		23L075FB	6F	23	69.73	68.97	79.5	55	-	25.4	38	14		
		24L075FB	6F	24	72.77	72.00	79.0	55	-	25.4	38	14		
		25L075FB	6F	25	75.80	75.04	83.0	58	-	25.4	38	14		
		26L075FB	6F	26	78.83	78.07	87.0	58	-	25.4	38	14		
		27L075FB	6F	27	81.86	81.10	91.0	58	-	25.4	38	14		
		28L075FB	6F	28	84.89	84.13	91.0	58	-	25.4	38	14		
		29L075FB	6F	29	87.93	87.16	91.0	58	-	25.4	38	14		
		30L075FB	6F	30	90.96	90.20	97.0	70	-	25.4	38	14		
		32L075FB	6F	32	97.02	96.26	102.0	70	-	25.4	38	14		
		Material: Gjutjärn Materiale: Cast Iron	Med Flänsar With Flanges	33L075FB	6F	33	100.05	99.29	112.0	70	-	25.4	38	14
				34L075FB	6F	34	103.08	102.32	115.0	70	-	25.4	38	14
				35L075FB	6F	35	106.12	105.35	115.0	70	-	25.4	38	14
				36L075FB	6F	36	109.15	108.39	120.0	70	-	25.4	38	14
				40L075FB	6WF	40	121.28	120.51	128.0	70	100	25.4	38	16
				41L075FB	6WF	41	124.31	123.55	135.0	70	103	25.4	38	16
				42L075FB	6WF	42	127.34	126.58	135.0	70	106	25.4	38	16
				44L075FB	6WF	44	133.40	132.64	142.0	70	112	25.4	38	16
				45L075FB	6WF	45	136.44	135.67	142.0	70	115	25.4	38	16
				47L075FB	6WF	47	142.50	141.74	150.0	70	121	25.4	38	16
48L075FB	6WF		48	145.53	144.77	150.0	70	124	25.4	38	16			
Utan Flänsar Without Flanges	49L075FB		6W	49	148.56	147.80	-	70	127	25.4	38	16		
	50L075FB		6W	50	151.60	150.83	-	70	130	25.4	38	16		
	52L075FB		6W	52	157.66	156.90	-	70	136	25.4	38	16		
	56L075FB		6W	56	169.79	169.02	-	70	149	25.4	38	16		
	57L075FB		6W	57	172.82	172.06	-	70	152	25.4	38	18		
	60L075FB		6W	60	181.91	181.15	-	75	160	25.4	45	18		
	65L075FB		6A	65	197.07	196.31	-	75	176	25.4	45	18		
	66L075FB		6A	66	200.11	199.34	-	75	179	25.4	45	18		
	72L075FB		6A	72	218.30	217.53	-	75	197	25.4	45	18		
	84L075FB	6A	84	254.68	253.92	-	75	233	25.4	45	18			
90L075FB	6A	90	272.87	272.11	-	75	252	25.4	45	18				
96L075FB	6A	96	291.06	290.30	-	75	269	25.4	45	18				
120L075FB	6A	120	363.83	363.07	-	75	342	25.4	45	18				