

KUGGREMSHJUL FÖRBORRADE, HTD

TIMING BELT PULLEYS STANDARD, HTD

HTD 20M-115

Utförande Version	Best. Nr. Code	Typ Type	Tandantal No. of teeth	Dp	De	Df	Dm	Di	F	L	e	d
Material: Gjutjärn Materiale: Cast iron	Med Flänsar With Flanges	34-20M-115FB 6F	34	216.45	212.13	240	165	-	136.5	168.5	-	32
		36-20M-115FB 6F	36	229.18	224.87	250	178	-	136.5	168.5	-	32
		38-20M-115FB 6F	38	241.92	237.60	265	181	-	136.5	168.5	-	32
		40-20M-115FB 6F	40	254.65	250.33	275	203	-	136.5	168.5	-	32
		44-20M-115FB 6F	44	280.11	275.79	300	210	-	136.5	168.5	-	32
		48-20M-115FB 6F	48	305.58	301.26	325	228	-	136.5	168.5	-	32
		52-20M-115FB 6F	52	331.04	326.72	350	228	-	136.5	168.5	-	32
		56-20M-115FB 6F	56	356.51	352.19	375	228	-	136.5	168.5	-	32
		60-20M-115FB 6WF	60	381.97	377.65	405	228	318	136.5	168.5	-	38
		64-20M-115FB 6WF	64	407.44	403.12	430	228	343	136.5	168.5	-	38
	68-20M-115FB 6WF	68	432.90	428.58	455	228	366	136.5	168.5	-	38	
	72-20M-115FB 6AF	72	458.37	454.05	480	228	435	136.5	168.5	-	38	
	80-20M-115FB 6AF	80	509.30	504.98	530	280	445	136.5	168.5	-	38	
	90-20M-115FB 6AF	90	572.96	568.64	595	280	508	136.5	168.5	-	38	
	112-20M-115FB 6A	112	713.01	708.70	-	280	648	136.5	168.5	-	38	
	144-20M-115FB 6A	144	916.73	912.41	-	300	852	136.5	168.5	-	44	
	168-20M-115FB 6A	168	1069.52	1065.21	-	300	1005	136.5	168.5	-	44	
	192-20M-115FB 6A	192	1222.31	1218.00	-	300	1158	136.5	168.5	-	48	
	216-20M-115FB 6A	216	1375.10	1370.78	-	300	1300	136.5	168.5	-	48	
	Utan Flänsar Without Flanges											

HTD 20M-170

Utförande Version	Best. Nr. Code	Typ Type	Tandantal No. of teeth	Dp	De	Df	Dm	Di	F	L	e	d
Material: Gjutjärn Materiale: Cast iron	Med Flänsar With Flanges	34-20M-170FB 6F	34	216.45	212.13	240	165	-	190.5	222.5	-	38
		36-20M-170FB 6F	36	229.18	224.87	250	178	-	190.5	222.5	-	38
		38-20M-170FB 6F	38	241.92	237.60	265	181	-	190.5	222.5	-	38
		40-20M-170FB 6F	40	254.65	250.33	275	203	-	190.5	222.5	-	38
		44-20M-170FB 6F	44	280.11	275.79	300	210	-	190.5	222.5	-	38
		48-20M-170FB 6F	48	305.58	301.26	325	240	-	190.5	222.5	-	38
		52-20M-170FB 6F	52	331.04	326.72	350	280	-	190.5	222.5	-	38
		56-20M-170FB 6F	56	356.51	352.19	375	280	-	190.5	222.5	-	38
		60-20M-170FB 6F	60	381.97	377.65	405	280	-	190.5	222.5	-	38
		64-20M-170FB 6F	64	407.44	403.12	430	280	-	190.5	222.5	-	38
	68-20M-170FB 6F	68	432.90	428.58	455	280	-	190.5	222.5	-	38	
	72-20M-170FB 10AF	72	458.37	454.05	480	280	394	190.5	190.5	-	38	
	80-20M-170FB 10AF	80	509.30	504.98	530	280	445	190.5	190.5	-	38	
	90-20M-170FB 10AF	90	572.96	568.64	595	280	508	190.5	190.5	-	38	
	112-20M-170FB 10A	112	713.01	708.70	-	300	648	190.5	190.5	-	38	
	144-20M-170FB 10A	144	916.73	912.41	-	300	852	190.5	190.5	-	44	
	168-20M-170FB 10A	168	1069.52	1065.21	-	350	1005	190.5	190.5	-	44	
	192-20M-170FB 10A	192	1222.31	1218.00	-	350	1158	190.5	190.5	-	48	
	216-20M-170FB 10A	216	1375.10	1370.78	-	350	1300	190.5	190.5	-	48	
	Utan Flänsar Without Flanges											