

KUGGREMSHJUL FÖRBORRADE, HTD

TIMING BELT PULLEYS STANDARD, HTD

HTD 20M-230

Utförande Version	Best. Nr. Code	Typ Type	Tandantal No. of teeth	Dp	De	Df	Dm	Di	F	L	e	d	
Material: Gjutjärn Materiale: Cast iron	Med Flänsar With Flanges	38-20M-230FB	6F	38	241.92	237.60	265	181	-	250.8	282.8	-	38
		40-20M-230FB	6F	40	254.65	250.33	275	203	-	250.8	282.8	-	38
		44-20M-230FB	6F	44	280.11	275.79	300	210	-	250.8	282.8	-	38
		48-20M-230FB	6F	48	305.58	301.26	325	228	-	250.8	282.8	-	38
		52-20M-230FB	6F	52	331.04	326.72	350	280	-	250.8	282.8	-	38
		56-20M-230FB	6F	56	356.51	352.19	375	280	-	250.8	282.8	-	38
		60-20M-230FB	6F	60	381.97	377.65	405	280	-	250.8	282.8	-	38
		64-20M-230FB	6F	64	407.44	403.12	430	300	-	250.8	282.8	-	38
		68-20M-230FB	6F	68	432.90	428.58	455	300	-	250.8	282.8	-	38
	72-20M-230FB	6F	72	458.37	454.05	480	300	-	250.8	282.8	-	38	
	Utan Flänsar Without Flanges	80-20M-230FB	10WF	80	509.30	504.98	530	300	445	250.8	250.8	-	38
		90-20M-230FB	10AF	90	572.96	568.64	595	300	508	250.8	250.8	-	38
		112-20M-230FB	10A	112	713.01	708.70	-	300	648	250.8	250.8	-	38
		144-20M-230FB	10A	144	916.73	912.41	-	350	852	250.8	250.8	-	44
		168-20M-230FB	10A	168	1069.52	1065.21	-	350	1005	250.8	250.8	-	44
		192-20M-230FB	10A	192	1222.31	1218.00	-	400	1158	250.8	250.8	-	48
		216-20M-230FB	10A	216	1375.10	1370.78	-	400	1300	250.8	250.8	-	48

HTD 20M-290

Utförande Version	Best. Nr. Code	Typ Type	Tandantal No. of teeth	Dp	De	Df	Dm	Di	F	L	e	d	
Material: Gjutjärn Materiale: Cast iron	Med Flänsar With Flanges	52-20M-290FB	6F	52	331.04	326.72	350	280	-	311.2	343.0	-	38
		56-20M-290FB	6F	56	356.51	352.19	375	280	-	311.2	343.0	-	38
		60-20M-290FB	6F	60	381.97	377.65	405	300	-	311.2	343.0	-	38
		64-20M-290FB	6F	64	407.44	403.12	430	300	-	311.2	343.0	-	38
		68-20M-290FB	6F	68	432.90	428.58	455	300	-	311.2	343.0	-	38
		72-20M-290FB	6F	72	458.37	454.05	480	300	-	311.2	343.0	-	44
		80-20M-290FB	6F	80	509.30	504.98	530	300	-	311.2	343.0	-	44
		90-20M-290FB	10WF	90	572.96	568.64	595	300	508	311.2	311.2	-	44
		112-20M-290FB	10A	112	713.01	708.70	-	350	648	311.2	311.2	-	48
	144-20M-290FB	10A	144	916.73	912.41	-	350	852	311.2	311.2	-	48	
	Utan Flänsar Without Flanges	168-20M-290FB	10A	168	1069.52	1065.21	-	400	1005	311.2	311.2	-	48
		192-20M-290FB	10A	192	1222.31	1218.00	-	400	1158	311.2	311.2	-	48
		216-20M-290FB	10A	216	1375.10	1370.78	-	400	1300	311.2	311.2	-	48

HTD 20M-340

Utförande Version	Best. Nr. Code	Typ Type	Tandantal No. of teeth	Dp	De	Df	Dm	Di	F	L	e	d	
Material: Gjutjärn Materiale: Cast iron	Med Flänsar With Flanges	52-20M-340FB	6F	52	331.04	326.72	350	280	-	362	394	-	38
		56-20M-340FB	6F	56	356.51	352.19	375	280	-	362	394	-	38
		60-20M-340FB	6F	60	381.97	377.65	405	300	-	362	394	-	38
		64-20M-340FB	6F	64	407.44	403.12	430	300	-	362	394	-	44
		68-20M-340FB	6F	68	432.90	428.58	455	300	-	362	394	-	44
		72-20M-340FB	6F	72	458.37	454.05	480	300	-	362	394	-	44
		80-20M-340FB	6F	80	509.30	504.98	530	300	-	362	394	-	44
		90-20M-340FB	10WF	90	572.96	568.64	595	350	508	362	394	-	48
		112-20M-340FB	10A	112	713.01	708.70	-	350	648	362	362	-	48
	144-20M-340FB	10A	144	916.73	912.41	-	400	852	362	362	-	48	
	Utan Flänsar Without Flanges	168-20M-340FB	10A	168	1069.52	1065.21	-	400	1005	362	362	-	48
		192-20M-340FB	10A	192	1222.31	1218.00	-	430	1158	362	362	-	48
		216-20M-340FB	10A	216	1375.10	1370.78	-	430	1300	362	362	-	48