

# KUGGREMSHJUL FÖR KONISK KLÄMBUSSNING, HTD

## TIMING BELT PULLEYS FOR TAPER BUSH, HTD

### HTD 8M-50

| Utförande<br>Version                             | Best. Nr.<br>Code               | Typ<br>Type | Tandantal<br>No. of teeth | Bussning<br>Bush | Max. axelhål<br>Max. Bore | Dp     | De     | Df     | Dm  | Di  | F   | S  | R   |      |
|--|---------------------------------|-------------|---------------------------|------------------|---------------------------|--------|--------|--------|-----|-----|-----|----|-----|------|
| Material:<br>Gjutjärn<br>Materiale:<br>Cast iron | Med Flänsar<br>With Flanges     | 28-8M-50F   | 4F                        | 28               | 1108                      | 25     | 71.30  | 70.08  | 75  | -   | 50  | 60 | 22  | 19.0 |
|  |                                 | 30-8M-50F   | 5F                        | 30               | 1615                      | 42     | 76.39  | 75.13  | 83  | -   | 58  | 60 | 38  | 22.0 |
|  |                                 | 32-8M-50F   | 5F                        | 32               | 1615                      | 42     | 81.49  | 80.16  | 87  | -   | 62  | 60 | 38  | 22.0 |
|  |                                 | 34-8M-50F   | 5F                        | 34               | 1615                      | 42     | 86.58  | 85.22  | 91  | -   | 65  | 60 | 38  | 22.0 |
|  |                                 | 36-8M-50F   | 5F                        | 36               | 1615                      | 42     | 91.67  | 90.30  | 97  | -   | 68  | 60 | 38  | 22.0 |
|  |                                 | 38-8M-50F   | 5F                        | 38               | 1615                      | 42     | 96.77  | 95.39  | 102 | -   | 72  | 60 | 38  | 22.0 |
|  |                                 | 40-8M-50F   | 4F                        | 40               | 2012                      | 50     | 101.86 | 100.49 | 112 | -   | 82  | 60 | 32  | 14.0 |
|  |                                 | 44-8M-50F   | 4F                        | 44               | 2012                      | 50     | 112.05 | 110.67 | 120 | -   | 91  | 60 | 32  | 14.0 |
|  |                                 | 48-8M-50F   | 4F                        | 48               | 2012                      | 50     | 122.23 | 120.86 | 128 | -   | 95  | 60 | 32  | 14.0 |
|  |                                 | 56-8M-50F   | 4F                        | 56               | 2517                      | 60     | 142.60 | 141.23 | 150 | -   | 116 | 60 | 45  | 7.5  |
|  |                                 | 64-8M-50F   | 4F                        | 64               | 2517                      | 60     | 162.97 | 161.60 | 168 | -   | 137 | 60 | 45  | 7.5  |
|  |                                 | 72-8M-50F   | 9WF                       | 72               | 2517                      | 60     | 183.35 | 181.97 | 192 | 125 | 158 | 60 | 45  | 7.5  |
|  | 80-8M-50F                       | 4           | 80                        | 3020             | 75                        | 203.72 | 202.35 | -      | -   | 180 | 60  | 51 | 4.5 |      |
|  | 90-8M-50F                       | 9W          | 90                        | 3020             | 75                        | 229.18 | 227.81 | -      | 170 | 204 | 60  | 51 | 4.5 |      |
|  | 112-8M-50F                      | 9W          | 112                       | 3020             | 75                        | 285.21 | 283.83 | -      | 170 | 260 | 60  | 51 | 4.5 |      |
|  | Utan Flänsar<br>Without Flanges | 144-8M-50F  | 9A                        | 144              | 3020                      | 75     | 366.69 | 365.52 | -   | 170 | 341 | 60 | 51  | 4.5  |
|  |                                 | 168-8M-50F  | 9A                        | 168              | 3020                      | 75     | 427.81 | 426.44 | -   | 170 | 402 | 60 | 51  | 4.5  |
|  |                                 | 192-8M-50F  | 9A                        | 192              | 3020                      | 75     | 488.92 | 487.55 | -   | 170 | 460 | 60 | 51  | 4.5  |

### HTD 8M-85

| Utförande<br>Version                             | Best. Nr.<br>Code               | Typ<br>Type | Tandantal<br>No. of teeth | Bussning<br>Bush | Max. axelhål<br>Max. Bore | Dp | De     | Df     | Dm  | Di  | F   | S  | R  |      |
|--|---------------------------------|-------------|---------------------------|------------------|---------------------------|----|--------|--------|-----|-----|-----|----|----|------|
| Material:<br>Gjutjärn<br>Materiale:<br>Cast iron | Med Flänsar<br>With Flanges     | 34-8M-85F   | 4F                        | 34               | 1615                      | 42 | 86.58  | 85.22  | 91  | -   | 65  | 95 | 38 | 28.5 |
|  |                                 | 36-8M-85F   | 4F                        | 36               | 1615                      | 42 | 91.67  | 90.30  | 97  | -   | 68  | 95 | 38 | 28.5 |
|  |                                 | 38-8M-85F   | 4F                        | 38               | 1615                      | 42 | 96.77  | 95.39  | 102 | -   | 72  | 95 | 38 | 28.5 |
|  |                                 | 40-8M-85F   | 4F                        | 40               | 2012                      | 50 | 101.86 | 100.49 | 112 | -   | 82  | 95 | 32 | 31.5 |
|  |                                 | 44-8M-85F   | 4F                        | 44               | 2012                      | 50 | 112.05 | 110.67 | 120 | -   | 91  | 95 | 32 | 31.5 |
|  |                                 | 48-8M-85F   | 4F                        | 48               | 2517                      | 60 | 122.23 | 120.86 | 128 | -   | 100 | 95 | 45 | 25.0 |
|  |                                 | 56-8M-85F   | 4F                        | 56               | 2517                      | 60 | 142.60 | 141.23 | 150 | -   | 117 | 95 | 45 | 25.0 |
|  |                                 | 64-8M-85F   | 4F                        | 64               | 2517                      | 60 | 162.97 | 161.60 | 168 | -   | 137 | 95 | 45 | 25.0 |
|  |                                 | 72-8M-85F   | 4F                        | 72               | 3020                      | 75 | 183.35 | 181.97 | 192 | -   | 158 | 95 | 51 | 22.0 |
|  |                                 | 80-8M-85F   | 4                         | 80               | 3020                      | 75 | 203.72 | 202.35 | -   | -   | 180 | 95 | 51 | 22.0 |
|  | Utan Flänsar<br>Without Flanges | 90-8M-85F   | 9W                        | 90               | 3020                      | 75 | 229.78 | 227.81 | -   | 170 | 204 | 95 | 51 | 22.0 |
|  |                                 | 112-8M-85F  | 9W                        | 112              | 3020                      | 75 | 285.21 | 283.83 | -   | 170 | 260 | 95 | 51 | 22.0 |
|  |                                 | 144-8M-85F  | 9A                        | 144              | 3030                      | 75 | 366.69 | 365.32 | -   | 170 | 341 | 95 | 76 | 9.5  |
|  |                                 | 168-8M-85F  | 9A                        | 168              | 3030                      | 75 | 427.81 | 426.44 | -   | 170 | 402 | 95 | 76 | 9.5  |
|  |                                 | 192-8M-85F  | 9A                        | 192              | 3030                      | 75 | 488.92 | 487.55 | -   | 170 | 460 | 95 | 76 | 9.5  |