

# KUGGREMSHJUL FÖR KONISK KLÄMBUSSNING, HTD

## TIMING BELT PULLEYS FOR TAPER BUSH, HTD

### HTD 14M-40

Utförande Version	Best. Nr. Code	Typ Type	Tandantal No. of teeth	Bussning Bush	Max. axelhål Max. Bore	Dp	De	Df	Dm	Di	F	S	R	
Material: Gjutjärn Materiale: Cast iron	Med Flänsar With Flanges	28-14M-40F	4F	28	2012	50	124.78	122.12	128	-	98	54	32	11.0
		29-14M-40F	4F	29	2012	50	129.23	126.57	150	-	100	54	32	11.0
		30-14M-40F	4F	30	2012	50	133.69	130.99	150	-	100	54	32	11.0
		32-14M-40F	4F	32	2012	50	142.60	139.88	158	-	104	54	32	11.0
		34-14M-40F	4F	34	2517	60	151.52	148.79	158	-	110	54	45	4.5
		36-14M-40F	4F	36	2517	60	160.43	157.68	168	-	120	54	45	4.5
		38-14M-40F	4F	38	2517	60	169.34	166.60	184	-	130	54	45	4.5
		40-14M-40F	4F	40	2517	60	178.25	175.49	192	-	138	54	45	4.5
		44-14M-40F	4F	44	3020	75	196.08	193.28	211	-	155	54	51	1.5
		48-14M-40F	4F	48	3020	75	213.90	211.11	226	-	170	54	51	1.5
	Utan Flänsar Without Flanges	56-14M-40F	9WF	56	3020	75	249.55	246.76	265	170	208	54	51	1.5
		64-14M-40F	9WF	64	3020	75	285.21	282.41	296	170	242	54	51	1.5
		72-14M-40F	9W	72	3020	75	320.86	318.06	-	170	280	54	51	1.5
		80-14M-40F	9A	80	3020	75	356.51	353.71	-	170	315	54	51	1.5
		90-14M-40F	9A	90	3020	75	401.07	398.28	-	170	360	54	51	1.5
		112-14M-40F	9A	112	3020	75	499.11	496.32	-	170	457	54	51	1.5
		144-14M-40F	9A	144	3020	75	641.71	638.92	-	170	600	54	51	1.5
		168-14M-40F	9A	168	3020	75	748.66	745.87	-	170	706	54	51	1.5
		192-14M-40F	9A	192	3020	75	855.62	852.82	-	170	813	54	51	1.5
		216-14M-40F	9A	216	3020	75	962.57	959.76	-	170	920	54	51	1.5

### HTD 14M-55

Utförande Version	Best. Nr. Code	Typ Type	Tandantal No. of teeth	Bussning Bush	Max. axelhål Max. Bore	Dp	De	Df	Dm	Di	F	S	R	
Material: Gjutjärn Materiale: Cast iron	Med Flänsar With Flanges	28-14M-55F	4F	28	2012	50	124.78	122.12	128	-	98	70	32	19.0
		29-14M-55F	4F	29	2012	50	129.23	126.57	150	-	100	70	32	19.0
		30-14M-55F	5F	30	2517	60	133.69	130.99	150	-	100	70	45	12.5
		32-14M-55F	5F	32	2517	60	142.60	139.88	158	-	108	70	45	12.5
		34-14M-55F	5F	34	2517	60	151.52	148.79	158	-	110	70	45	12.5
		36-14M-55F	5F	36	2517	60	160.43	157.68	168	-	120	70	45	12.5
		38-14M-55F	5F	38	2517	60	169.34	166.60	184	-	130	70	45	12.5
		40-14M-55F	4F	40	2517	60	178.25	175.49	192	-	138	70	45	12.5
		44-14M-55F	4F	44	3020	75	196.08	193.28	211	-	155	70	51	9.5
		48-14M-55F	4F	48	3020	75	213.90	211.11	226	-	170	70	51	9.5
	Utan Flänsar Without Flanges	56-14M-55F	9WF	56	3020	75	249.55	246.76	265	170	208	70	51	9.5
		64-14M-55F	9WF	64	3020	75	285.21	282.41	296	170	242	70	51	9.5
		72-14M-55F	9W	72	3020	75	320.86	318.06	-	170	280	70	51	9.5
		80-14M-55F	9A	80	3020	75	356.51	353.71	-	170	315	70	51	9.5
		90-14M-55F	9A	90	3020	75	401.07	398.28	-	170	360	70	51	9.5
		112-14M-55F	9A	112	3020	75	499.11	496.32	-	170	457	70	51	9.5
		144-14M-55F	9A	144	3020	75	641.71	638.92	-	170	600	70	51	9.5
		168-14M-55F	9A	168	3020	75	748.66	745.87	-	170	706	70	51	9.5
		192-14M-55F	9A	192	3020	75	855.62	852.82	-	170	813	70	51	9.5
		216-14M-55F	7A	216	3525	90	962.57	959.76	-	190	920	70	89	9.5