


KUGGREMMAR FÖR HTD, PROFIL 3M, 5M, 8M, 14M, 20M

TIMING BELT FOR HTD, PROFILE 3M, 5M, 8M, 14M, 20M

Material: Neoprengummi med glasfiberkord.
Kuggar förstärkta med nylonväv.

Material: Neopren rubber with glasfiberCORD.
Nylon fabric on the tooth surface.



5M-DT

Längd mm Length mm	Antal tänder No. of teeth
425 DT	85
475 DT	95
500 DT	100
600 DT	120
615 DT	123
640 DT	128
670 DT	134
700 DT	140
755 DT	151
800 DT	160
835 DT	167
890 DT	178
935 DT	186
1100 DT	220
1200 DT	240

P	5.00
H1	2.06
H2	1.15

8M-DT

Längd mm Length mm	Antal tänder No. of teeth
480 DT	60
560 DT	70
600 DT	75
640 DT	80
720 DT	90
800 DT	100
880 DT	110
960 DT	120
1040 DT	130
1120 DT	140
1200 DT	150
1280 DT	160
1360 DT	170
1440 DT	180
1600 DT	200
1760 DT	220
1800 DT	225
2000 DT	250
2400 DT	300
2600 DT	325
2800 DT	350

P	8.00
H1	3.40
H2	1.37

14M-DT

Längd mm Length mm	Antal tänder No. of teeth
1610 DT	115
1778 DT	127
1890 DT	135
2100 DT	150
2310 DT	165
2450 DT	175
2590 DT	185
2800 DT	200
3150 DT	225

P	14.00
H1	6.10
H2	2.80

Standard bredder / Standard widths

Typ 5M / Type 5M: 9 mm, 15 mm, 25 mm

Typ 8M / Type 8M: 20 mm, 30 mm, 50 mm, 85 mm

Typ 14M / Type 14M: 40 mm, 55 mm, 85 mm, 115 mm, 170 mm