

# KUGGREMSHJUL FÖR KONISK KLÄMBUSSNING L, H, XH

## TIMING BELT PULLEYS FOR TAPER BUSH L, H, XH

### L 050 - 3/8" (9.525 mm)

Utförande Version		Best Nr. Code	Typ Type	Bussning Bush	Max. Axelhål Max. Bore	Dp	De	Df	Dm	Di	F	S	R
Material: Stål Material: Steele		18 L 050F	8F	1108	28	54.57	53.81	60.0	43	-	19.0	22.0	3.0
		19 L 050F	8F	1108	28	57.61	56.84	62.5	43	-	19.0	22.0	3.0
		20 L 050F	8F	1108	28	60.64	59.88	67.0	48	-	19.0	22.0	3.0
		21 L 050F	8F	1108	28	63.67	62.91	70.0	48	-	19.0	22.0	3.0
Material: Gjutjärn Material: Cast Iron	Med Flänsar With Flanges	22 L 050F	8F	1108	28	66.70	65.94	75.0	51	-	19.0	22.0	3.0
		23 L 050F	8F	1108	28	69.73	68.97	79.5	54	-	19.0	22.0	3.0
		24 L 050F	8F	1108	28	72.77	72.00	79.5	54	-	19.0	22.0	3.0
		25 L 050F	8F	1108	28	75.80	75.04	87.0	56	-	19.0	22.0	3.0
		26 L 050F	8F	1108	28	78.83	78.07	87.0	60	-	19.0	22.0	3.0
		27 L 050F	8F	1108	28	81.86	81.10	91.0	65	-	19.0	22.0	3.0
		28 L 050F	8F	1108	28	84.89	84.13	91.0	65	-	19.0	22.0	3.0
		30 L 050F	8F	1108	28	90.96	90.20	97.0	70	-	19.0	22.0	3.0
		32 L 050F	8F	1108	28	97.02	96.26	102.0	74	-	19.0	22.0	3.0
		36 L 050F	8F	1108	28	109.15	108.39	120.0	87	-	19.0	22.0	3.0
		40 L 050F	8F	1210	35	121.28	120.51	128.0	97	-	19.0	25.0	3.0
		48 L 050F	8WF	1210	35	145.53	144.77	150.0	88	124	19.0	25.0	3.0
Material: Gjutjärn Material: Cast Iron	Utan Flänsar Without Flanges	60 L 050F	7W	1610	42	181.91	181.15	-	92	166	19.0	25.0	3.0
		72 L 050F	7A	1610	42	218.30	217.53	-	92	202	19.0	25.0	3.0
		84 L 050F	7A	1610	42	254.68	253.90	-	92	236	19.0	25.0	3.0
		96 L 050F	7A	2012	50	291.06	290.30	-	106	270	19.0	32.0	6.5
		120 L 050F	7A	2012	50	363.83	363.07	-	106	343	19.0	32.0	6.5

### L 075 - 3/8" (9.525 mm)

Utförande Version		Best Nr. Code	Typ Type	Bussning Bush	Max. Axelhål Max. Bore	Dp	De	Df	Dm	Di	F	S	R
Material: Stål Material: Steele		18 L 075F	3F	1108	28	54.57	53.81	60.0	-	-	25.0	22.0	-
		19 L 075F	3F	1108	28	57.61	56.84	62.5	-	-	25.0	22.0	-
		20 L 075F	3F	1108	28	60.64	59.88	67.0	-	-	25.0	22.0	-
		21 L 075F	3F	1108	28	63.67	62.91	70.0	-	-	25.0	22.0	-
Material: Gjutjärn Material: Cast Iron	Med Flänsar With Flanges	22 L 075F	3F	1108	28	66.70	65.94	75.0	-	-	25.0	22.0	-
		23 L 075F	3F	1108	28	69.73	68.97	79.5	-	-	25.0	22.0	-
		24 L 075F	3F	1108	28	72.77	72.00	79.5	-	-	25.0	22.0	-
		25 L 075F	3F	1108	28	75.80	75.04	87.0	-	-	25.0	22.0	-
		26 L 075F	3F	1108	28	78.83	78.07	87.0	-	-	25.0	22.0	-
		27 L 075F	3F	1108	28	81.86	81.10	91.0	-	-	25.0	22.0	-
		28 L 075F	3F	1108	28	84.89	84.13	91.0	-	-	25.0	22.0	-
		30 L 075F	3F	1108	28	90.96	90.20	97.0	-	-	25.0	22.0	-
		32 L 075F	3F	1108	28	97.02	96.26	102.0	-	-	25.0	22.0	-
		36 L 075F	3F	1210	35	109.15	108.39	120.0	-	-	25.0	25.0	-
		40 L 075F	3F	1210	35	121.28	120.51	128.0	-	-	25.0	25.0	-
		48 L 075F	3WF	1610	42	145.53	144.77	150.0	92	125	25.0	25.0	-
Material: Gjutjärn Material: Cast Iron	Utan Flänsar Without Flanges	60 L 075F	3W	1610	42	181.91	181.15	-	92	166	25.0	25.0	-
		72 L 075F	3A	1610	42	218.30	217.53	-	92	202	25.0	25.0	-
		84 L 075F	7A	2012	50	254.68	253.90	-	106	236	25.0	32.0	3.5
		96 L 075F	7A	2012	50	291.06	290.30	-	106	270	25.0	32.0	3.5
		120 L 075F	7A	2012	50	363.83	363.07	-	106	343	25.0	32.0	3.5

### L 100 - 3/8" (9.525 mm)

Utförande Version		Best Nr. Code	Typ Type	Bussning Bush	Max. Axelhål Max. Bore	Dp	De	Df	Dm	Di	F	S	R
Material: Stål Material: Steele		18 L 100F	5F	1108	28	54.57	53.81	60.0	-	38	31.0	22.0	9.0
		19 L 100F	5F	1108	28	57.61	56.84	62.5	-	38	31.0	22.0	9.0
		20 L 100F	5F	1108	28	60.64	59.88	67.0	-	45	31.0	22.0	9.0
		21 L 100F	5F	1108	28	63.67	62.91	70.0	-	47	31.0	22.0	9.0
Material: Gjutjärn Material: Cast Iron	Med Flänsar With Flanges	22 L 100F	5F	1108	28	66.70	65.94	75.0	-	51	31.0	22.0	9.0
		23 L 100F	5F	1108	28	69.73	68.97	79.5	-	54	32.0	22.0	10.0
		24 L 100F	5F	1108	28	72.77	72.00	79.5	-	54	32.0	22.0	10.0
		25 L 100F	5F	1108	28	75.80	75.04	87.0	-	56	32.0	22.0	10.0
		26 L 100F	5F	1108	28	78.83	78.07	87.0	-	60	32.0	22.0	10.0
		27 L 100F	5F	1108	28	81.86	81.10	91.0	-	62	32.0	22.0	10.0
		28 L 100F	5F	1108	28	84.89	84.13	91.0	-	65	32.0	22.0	10.0
		30 L 100F	5F	1210	35	90.96	90.20	97.0	-	71	32.0	25.0	7.0
		32 L 100F	5F	1210	35	97.02	96.26	102.0	-	75	32.0	25.0	7.0
		36 L 100F	5F	1210	35	109.15	108.39	120.0	-	89	32.0	25.0	7.0
		40 L 100F	5F	1610	42	121.28	120.51	128.0	-	101	32.0	25.0	7.0
		48 L 100F	5WF	1610	42	145.53	144.77	150.0	92	124	32.0	25.0	7.0
Material: Gjutjärn Material: Cast Iron	Utan Flänsar Without Flanges	60 L 100F	9W	1610	42	181.91	181.15	-	92	166	32.0	25.0	3.5
		72 L 100F	3A	2012	50	218.30	217.53	-	106	202	32.0	32.0	-
		84 L 100F	3A	2012	50	254.68	253.90	-	106	236	32.0	32.0	-
		96 L 100F	3A	2012	50	291.06	290.30	-	106	270	32.0	32.0	-
		120 L 100F	3A	2012	50	363.83	363.07	-	106	343	32.0	32.0	-