



SNÄCKSKRUVAR OCH SNÄCKHJUL

WORMS AND WORM-WHEELS

1 Ingång vänster 1 Lead left-handed	Best Nr. Code	Antal tänder No. of teeth	d	da	N	n	b	L	a	B-H7	
Modul 0.5	B 0520 1l	20	10.0	11.4	8	5	3.0	8.0	8.50	3	
	B 0525 1l	25	12.5	14.0	10	5	3.0	8.0	9.75	4	
	B 0540 1l	40	20.0	21.5	10	5	3.0	8.0	13.50	4	
Modul 0.75	B 0718 1l	18	13.5	15.4	10	6	3.0	9.0	11.00	4	
	B 0720 1l	20	15.0	16.9	10	6	3.0	9.0	11.75	4	
	B 0760 1l	60	45.0	47.0	15	6	3.0	9.0	26.75	4	
Modul 1.0	B 1016 1l	16	16.0	18.7	12	8	6.5	14.5	15.00	5	
	B 1018 1l	18	18.0	20.7	12	8	6.5	14.5	16.00	5	
	B 1020 1l	20	20.0	22.7	16	8	6.5	14.5	17.00	5	
	B 1025 1l	25	25.0	27.7	16	8	6.5	14.5	19.50	5	
	B 1030 1l	30	30.0	32.7	16	10	6.5	16.5	22.00	6	
	B 1035 1l	35	35.0	37.7	16	10	6.5	16.5	24.50	6	
	B 1040 1l	40	40.0	42.7	20	10	6.5	16.5	27.00	6	
	B 1050 1l	50	50.0	52.7	20	10	6.5	16.5	32.00	6	
	B 1060 1l	60	60.0	62.5	30	10	6.5	16.5	37.00	6	
	B 1075 1l	75	75.0	77.7	30	10	6.5	16.5	44.50	6	
	B 10100 1l	100	100.0	102.7	30	12	6.5	18.5	57.00	6	
	Modul 1.5	B 1516 1l	16	24.0	28.4	20	8	12.0	28.0	24.50	8
		B 1518 1l	18	27.0	31.4	20	8	12.0	28.0	26.00	8
B 1520 1l		20	30.0	34.4	24	8	12.0	28.0	27.50	10	
B 1525 1l		25	37.5	41.9	30	8	12.0	28.0	31.25	10	
B 1530 1l		30	45.0	49.4	30	8	12.0	28.0	35.00	10	
B 1540 1l		40	60.0	63.4	30	10	12.0	32.0	42.50	10	
B 1550 1l		50	75.0	79.4	30	10	12.0	32.0	50.00	10	
B 1560 1l		60	90.0	94.4	40	10	12.0	32.0	57.50	12	
B 1575 1l		75	112.5	116.9	40	10	12.0	32.0	68.75	12	
Modul 2.0		B 2016 1l	16	32.0	37.7	25	8	14.0	30.0	32.00	8
	B 2018 1l	18	36.0	41.7	25	8	14.0	30.0	34.00	10	
	B 2020 1l	20	40.0	45.7	30	10	14.0	34.0	36.00	12	
	B 2025 1l	25	50.0	55.7	35	10	14.0	34.0	41.00	12	
	B 2030 1l	30	60.0	65.7	40	10	14.0	34.0	46.00	12	
	B 2040 1l	40	80.0	85.7	40	10	14.0	34.0	56.00	12	
	B 2048 1l	48	96.0	102.0	*35	12	16.0	28.0	64.00	20	
	B 2050 1l	50	100.0	105.7	40	10	14.0	34.0	66.00	12	
	B 2060 1l	60	120.0	125.7	50	10	14.0	34.0	76.00	12	



Material: Brons CuSn12Pb

* Ensidigt nav

Material: Brons CuSn12Pb

* One-sided hub

På förfrågan

1 ingång modul 3.0-6.0

2 ingångar vänster modul 0.5-6.0

On request

1 lead left-handed modul 0.5-6.0

2 leads left-handed modul 0.5-6.0