

VINKELVÄXLAR

ANGULAR TRANSMISSION UNITS

Typ / Type 2020

2-vägs rak manuellt reversibel vinkelväxel
 2-way manual-disengaging/reversing straight line unit

Utväxling Gear ratio	Best Nr. Code
1 : 1	202011

Vikt / Weight 5.1 kg
 Oljesmord / Oil lubrication 140 gr

Typ Type	Max ingående effekt på axel "A" vid 1400 r/m Max input power, shaft "A" at 1400 RPM		Max utgående moment i da Nm Max output torque in da Nm	
	kW	HP	B	C
2019	2.25	3	1.550	-
2020	2.25	3	1.550	-
2023	2.25	3	0.755	0.755

Viktigt: Växling kan endast göras i stillstånd, dock om endast små masskrafter på både in och utgående axlar kan växling göras vid varvtal upp till max 200 r/m.

Note: Manual engagement and disengagement can only be carried out when all shafts are stationary (unless the both driving and driven inertias are small and the speed do not exceed 200 RPM).

Rekommenderade smörjolja Alternative recommended lubricants

TOTAL	ESSO	BP	IP	MOBIL
TM 80W/90	GEAR OIL GX 80W/90	HYPOGEAR 80W/90 EP	PONTIAX HD 80W/90	MOBILUBE HD 80W/90
CARTER EP 150	SPARTAM EP 150	GRXP 150	MELLANA 150	MOBILGEAR 629